Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations Revision Date: 06/09/2015 Date of issue: 05/05/2015

Version: 1.1

Revision Date: 06/09/2015 Date	of issue: 05/05/2015	Version: 1.1
SECTION 1: IDENTIFICATION		
1.1. Product Identifier		
Product Name: Nettoyant Lustrant 2		
1.2. Intended Use of the Prod	uct	
Polishing Compound.		
c .	phone of the Responsible Party	
Company		
SAVONS EVY 3460, 39e Avenue, Mon	tréal, QC H1A 3V1	
T 514-642-9920		
savonsevy.com		
1.4. Emergency Telephone Number 800-424-9300	Emergency Number :	
1.4. Emergency Telephone Nu		
Emergency Number : 800-424-93		
	- TOLL FREE 24 HOUR EMERGENCY TELEPHON	IE NUMBER
SECTION 2: HAZARDS IDENTIFIC		
2.1. Classification of the Subs	tance or Mixture	
Classification (GHS-US)		
Skin Irrit. 3 H316		
Flamm. 4. H227		
Eye irritant 2b. H320 Full text of H-phrases: see section 16		
2.2. Label Elements		
GHS-US Labeling		
Hazard Pictograms (GHS-US)	:	
Signal Word (GHS-US)	: Warning	
Hazard Statements (GHS-US)	: H227 Combustible liquid	
	H316 – Causes mild skin irritation.	
	H320 – Causes eye irritation	
		No successione
Precautionary Statements (GHS-US)	: P210 Keep away from flames and hot surf P264 - Wash hands, forearms, and other e	-
	P273 - Avoid release to the environment.	sposed areas thoroughly after handling.
	P280 - Wear protective gloves, protective	clothing and eve protection
		plenty of water. Take off contaminated clothing
	and wash before reuse.	
	P332+P313 - If skin irritation occurs: Get n	nedical advice/attention.
	P370 + P378 In case of fire: Use fire exting	
	P501 - Dispose of contents/container in ac	-
	territorial, provincial, and international re-	gulations.
2.3. Other Hazards		
Exposure may aggravate those with p	re-existing eye, skin, or respiratory conditions	

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US) No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

3.2. Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Water	(CAS No) 7732-18-5	Q.S to 100	Not classified
Petroleum distillates, hydrotreated light	(CAS No) 64742-47-8	<40	Flam. Liq. 3, H226
			Skin Irrit. 2, H315
			STOT SE 3, H336
			Asp. Tox. 1, H304
Kaolin, calcined	(CAS No) -92704-41-1	<20	Not classified
Siloxanes and Silicones, di-Me	(CAS No) 63148-62-9	<20	Not classified
Glycerin	(CAS No) 56-81-5	<20	Not classified

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible). **Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water or soap and water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Causes skin irritation.

Inhalation: May cause respiratory irritation.

Skin Contact: Causes skin irritation. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Eye Contact: May cause eye irritation.

Ingestion: May be harmful if ingested in large quantities.

Chronic Symptoms: None expected under normal conditions of use.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Dry chemical, carbon dioxide, foam, water spray.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive. **Reactivity:** Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. **Hazardous Combustion Products**: Carbon oxides (CO, CO₂).

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing (vapor, mist, spray).

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. **Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

7.3. Specific End Use(s)

Polishing compound.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

Petroleum distillates, hydrotreated light (64742-47-8)		
British Columbia	OEL TWA (mg/m ³)	200 mg/m ³ (application restricted to conditions in which there are negligible
		aerosol exposures)
Kaolin, calcined (92704-	-41-1)	
Mexico	OEL TWA (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA)	15 mg/m ³ (total dust)
	(mg/m³)	5 mg/m ³ (respirable fraction)
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica)
Nunavut	OEL STEL (mg/m ³)	20 mg/m ³
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³
Northwest Territories	OEL STEL (mg/m ³)	20 mg/m ³
Northwest Territories	OEL TWA (mg/m³)	10 mg/m ³
Québec	VEMP (mg/m ³)	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-total dust)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³ (Al2O3)
Yukon	OEL TWA (mg/m ³)	30 mppcf (Al2O3)
Glycerin (56-81-5)		
Mexico	OEL TWA (mg/m ³)	10 mg/m ³ (mist)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

USA OSHA	OSHA PEL (TWA)	15 mg/m ³ (mist, total particulate)
	(mg/m³)	5 mg/m ³ (mist, respirable fraction)
Alberta	OEL TWA (mg/m³)	10 mg/m³ (mist)
British Columbia	OEL TWA (mg/m³)	10 mg/m³ (mist)
New Brunswick	OEL TWA (mg/m³)	10 mg/m³ (mist)
Nunavut	OEL STEL (mg/m ³)	20 mg/m³ (mist)
Nunavut	OEL TWA (mg/m ³)	10 mg/m³ (mist)
Northwest Territories	OEL STEL (mg/m ³)	20 mg/m³ (mist)
Northwest Territories	OEL TWA (mg/m³)	10 mg/m³ (mist)
Ontario	OEL TWA (mg/m ³)	10 mg/m³ (mist)
Québec	VEMP (mg/m ³)	10 mg/m³ (mist)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³ (mist)
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m³ (mist)
Yukon	OEL TWA (mg/m³)	30 mppcf (mist)

8.2. Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective goggles. Gloves. Protective clothing.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. **Environmental Exposure Controls:** Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink or smoke during use.	

SECTION	ON 9: PHYSICAL AND CHEMICAL PROPERTIES
0 1	Information on Pasis Dhysical and Chamical Dranarties

9.1. Information on Basic Physical and Chemical Properties		
Physical State	: Liquid	
Appearance	: CREAMY LIQUID,	
	#4212 -GRAY	
Odor	: Hydrocarbon-Fruity odor	
Odor Threshold	: Not available	
рН	: Not available	
Evaporation Rate	: Not available	
Melting Point	: Not available	
Freezing Point	: 18 °F (-7.78 °C)	
Boiling Point	: 210 - 212 °F (98.9 - 100 °C)	
Flash Point	: 176°F ASTM D93- Procedure B (Pensky Marten closed cup)	
Auto-ignition Temperature	: Not available	
Decomposition Temperature	: Not available	
Flammability (solid, gas)	: Not available	
Lower Flammable Limit	: 1%	
Upper Flammable Limit	: 7%	
Vapor Pressure	: Not available	
Relative Vapor Density at 20 °C	: Not available	

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 20	12 / Pulos And Posulations	
	-	
Relative Density :	Not available	
Specific Gravity	1.00 - 1.45	
Solubility	Dispersible	
Partition Coefficient: N-Octanol/Water	Not available	
Viscosity	Not available	
Viscosity, Dynamic	14000 cP	
Explosion Data – Sensitivity to Mechanical Impact	Not expected to present an explosion hazard due to mechanical impact	
Explosion Data – Sensitivity to Static Discharge	Not expected to present an explosion hazard due to static discharge	
SECTION 10: STABILITY AND REACTIVITY		
10.1. Reactivity: Hazardous reactions will not occu	ir under normal conditions.	
10.2. Chemical Stability: Stable under recommended	ded handling and storage conditions (see section 7).	
10.3. Possibility of Hazardous Reactions: Hazardo	bus polymerization will not occur.	
10.4. Conditions to Avoid: Direct sunlight. Extreme	ely high or low temperatures. Incompatible materials.	
10.5. Incompatible Materials: Strong acids. Strong	y bases. Strong oxidizers.	
10.6. Hazardous Decomposition Products: Carbon	oxides (CO, CO ₂).	
SECTION 11: TOXICOLOGICAL INFORMATION		
11.1. Information on Toxicological Effects - Proc	duct	
Acute Toxicity: Not classified		
LD50 and LC50 Data: Not available		
Skin Corrosion/Irritation: Causes skin irritation		
Serious Eye Damage/Irritation: Not classified		
Respiratory or Skin Sensitization: Not classified		
Germ Cell Mutagenicity: Not classified		
Teratogenicity: Not classified		
Carcinogenicity: Not classified		
Specific Target Organ Toxicity (Repeated Exposure): No	nt classified	
Reproductive Toxicity: Not classified		
Specific Target Organ Toxicity (Single Exposure): Not cl	assified	
Aspiration Hazard: Not classified		
Symptoms/Injuries After Inhalation: May cause respira	tory irritation	
Symptoms/Injuries After Skin Contact: Causes skin irritation. Symptoms may include: Redness, pain, swelling, itching, burning,		
dryness, and dermatitis		
Symptoms/Injuries After Eye Contact: May cause eye ir	rritation	
Symptoms/Injuries After Ingestion: May be harmful if ingested in large quantities		
Chronic Symptoms: None expected under normal conditions of use		
11.2. Information on Toxicological Effects - Ingredient(s)		
LD50 and LC50 Data:		
Petroleum distillates, hydrotreated light (64742-47-8)		
LD50 Oral Rat	> 5000 mg/kg	
LD50 Dermal Rabbit	> 2000 mg/kg	
LC50 Inhalation Rat	> 5.2 mg/l/4h	
Kaolin, calcined (92704-41-1)	· · · · ·	
LD50 Oral Rat	> 2000 mg/kg	
Glycerin (56-81-5)		
LD50 Oral Rat	27.2 g/kg	

> 10 g/kg

> 90000 mg/kg

> 570 mg/m³ (Exposure time: 1 h)

05/05/2015

LD50 Dermal Rabbit

LC50 Inhalation Rat

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Petroleum distillates, hydrotreated light (64742-47-8)		
LC50 Fish 1	Not toxic to aquatic organisms (fish, daphnia, algae) up to water solubility.	
LC 50 Fish 2	Not toxic to aquatic organisms (fish, daphnia, algae) up to water solubility.	
Kaolin, calcined (92704-41-1)		
LC50 Fish 1	> 100 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])	
EC50 Daphnia 1	> 1 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
Glycerin (56-81-5)		
LC50 Fish 1	54000 (51000 - 57000) mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])	
12.2. Persistence and Degradability		
Siloxanes and Silicones, di-Me (63148-62-9)		
Persistence and Degradability	Not established.	

12.3. Bioaccumulative Potential

Petroleum distillates, hydrotreated light (64742-47-8)		
BCF Fish 1	61 - 159	
Siloxanes and Silicones, di-Me (63148-62-9)		
Bioaccumulative Potential	Not established.	
Glycerin (56-81-5)		
BCF Fish 1	(no bioaccumulation)	
Log Pow	-1.76	

12.4. Mobility in Soil Not available

12.5. Other Adverse Effects Not available

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Sewage Disposal Recommendations: This material is hazardous to the aquatic environment. Keep out of sewers and waterways. Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT	Not regulated for transport
------------------------------	-----------------------------

- 14.2. In Accordance with IMDG Not regulated for transport
- 14.3. In Accordance with IATA Not regulated for transport
- 14.4. In Accordance with TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Nettoyant Lustrant 2		
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
Petroleum distillates, hydrotreated light (64742-47-8)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
OSHA Hazards (HCS 1994)		
Combustible liquid.		
TSCA Inventory Listing		
<u>Components</u>	<u>CAS-No.</u>	
Distillates, petroleum, hydrotreated light	64742-47-8	
SARA 302 Status		
SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.		
SARA 311/312 Classification		

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations	
"Fire hazard", "Immediate (acute) health hazard"	
SARA 313 Chemical	
SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De	
Minimis) reporting levels established by SARA Title III, Section 313.	
US. EPA CERCLA Hazardous Substances (40 CFR 302)	
None	
International Regulations	
WHMIS Classification	
Class B, Division 3: Combustible liquid.	
European Union	
Classification according to Regulation (EU) 1272/2008.	
Aspiration hazard, Category 1	
Repeated exposure may cause skin dryness or cracking.	
Australia. Inventory of Chemical Substances (AICS)Listed	
Japan. Inventory of Existing and New Chemical Substances (ENCS)Listed	
New Zealand. Inventory of Chemicals (NZIoC)Listed	
Switzerland. Inventory of Notified New Substances (CHINV)Listed	
Taiwan. National Existing Chemical Inventory (NECI)Listed	
Kaolin, calcined (92704-41-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
SARA Section 313 - Emission Reporting	1.0 % (fibrous forms)
Siloxanes and Silicones, di-Me (63148-62-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Glycerin (56-81-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	Y2 - Y2 - indicates an exempt polymer that is a polyester and is made
	only from reactants included in a specified list of low concern reactants
	that comprises one of the eligibility criteria for the exemption rule.
Water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. US State Regulations

Kaolin, calcined (92704-41-1)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

U.S. - Pennsylvania - RTK (Right to Know) List

Glycerin (56-81-5)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date

: 06/09/2015

Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Party Responsible for the Preparation of This Document

SAVONS EVY - 3460, 39e Avenue, Montréal, QC H1A 3V1 T 514-642-9920 - savonsevy.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012